ORIENT POWER

Technical data sheet

ITEM	PROVIDED	
General		
Type	**S-1000/20/0.4 kV**	**SL-1000/20/0.4 kV**
	1. **45**℃	1. **45**℃
Standard	IEC 60076	IEC 60076
Equipment tag No.		
Location	Outdoor	Outdoor
Design Ambient Air Temp.	Min:-25°C, Max: 45°C	Min:-25°C, Max: 45°C
Performance		
Type	**S-1000/20/0.4 kV**	**SL1000/20/0.4 kV**
Rated Voltage (kV)	20 ± 2x2.5% / 0.4 KV	20 ± 2x2.5% / 0.4 KV
Rated Power (HV/LV) (KVA)	1000	1000
Rated current (HV/LV) (A)	28.9 / 1444.3 A	28.9 / 1444.3 A
Tapping	Off-load	Off-load
Tapping range	±2x2.5%	±2x2.5%
Taping positions	5	5
Tapping location	HV WINDING.	HV WINDING.
Rated Frequency	50Hz	50Hz
Cooling Method	ONAN	ONAN
No load losses	Tier 2	Tier 2
Load losses	Tier 2	Tier 2
Vector group	Dyn11	Dyn11
Winding material	Cu	AL
Sound level	70 dB(A) Sound pressure level	70 dB(A) Sound pressure level
Impedance		
HV- LV	5%	5%
Insulation level		

This document is the property of AMIRAL and shall not be disclosed to third parties or reproduced without permission of the owner.

HV winding	Basic Lightning impulse	125kV	125kV
	Power frequency withstand voltage	50kV	50kV
LV windin	Basic Lightning impulse	-	-
	Power frequency withstand voltage	3kV	3kV
Temperature rise			
Winding Average K		60 K	60 K
Top oil K		55 K	55 K

This document is the property of AMIRAL and shall not be disclosed to third parties or reproduced without permission of the owner.